

Autospeed Micro Bangers

NATIONAL BANGER RULES APPLY

Additional rules re Micro Bangers:

Distributor Guards

Distributor guards are permitted on an engine that has a front facing distributor – i.e. a series engine.

The maximum width of the guard is 9", with a maximum thickness of ¼ ".

The guard may be for the full depth of the engine, bolted or welded to the sub-frame and/or gearbox, and at the top, braced back to the front of the head, using box iron to a maximum size of 1" x 1".

Metro Sub Frames

Metro rear sub frames may be secured by an additional two bolts, as a secondary fixing.

Engine Size

1500cc maximum

Eligible Cars

Cars for Micro Bangers should be Mini, Metro, Fiesta, Nova, Renault 5 size.

Not acceptable for Micro Bangers – Ford Escort, Vauxhall Astra, Fiat Tipo, Nissan Cherry, Hyundai Pony, Toyota Corolla.

Listed below are eligible cars.

IF YOU HAVE A CAR WHICH DOES NOT FEATURE ON THE LIST, BUT WHICH YOU CONSIDER FITS THE REQUIREMENT OF A MICRO BANGER, PLEASE OBTAIN CONFIRMATION FROM EDDIE JAMES (07977 883963) BEFORE YOU BEGIN PREPARATION OF THE CAR.

Allegro
Austin 1100
Austin 1300
Austin A30
Austin A40
Citroen AX
Citroen Visa
Fiat Panda
Fiat Uno
Ford Anglia
Ford Fiesta
Ford KA

Hillman Imp
Kia Pride
Mazda 121
Metro
Mini
Morris 1000
Nissan Micra
Nova
Peugeot 106
Peugeot 205
Proton Pasona
Renault 5

Riley Elf
Rover Metro
Skoda Favorit
Sunbeam Stiletto
Suzuki Swift
Toyota Starlet
Triumph Acclaim
VW Beetle
VW Polo
Wolsley 1500
Wolsley Hornet